



TEXAS EQUIPMENT

Mobile Column Lifts Recommended Battery Specifications

United States

3301 W MacArthur Blvd
Santa Ana, CA 92704 USA
Tel: +1 (949) 333-3800
Fax: +1 (949) 333-3804

United Arab Emirates

Saif Zone T5-008
Sharjah, UAE
Tel: +971 (06) 552 98 60
Fax: +971 (06) 552 98 61

Egypt

AutoMechanica
15th of May Street
Shoubra Al-Khaimah 13793
Tel: +20 115 808 5046



All DC and Wireless DC Mobile Column Lift models require two long-life deep-cycle batteries in combination with the supplied onboard battery charger on each column. Customer needs to supply batteries meeting below requirements to ensure proper operation.

Battery Requirement

Group 27 deep-cycle marine type battery with 625 MCA rating
180 AMP reserve, 105 AMP hour rating

Specifications:

1. Type: Maintenance-free, deep-cycle lead-acid battery
2. Rated Voltage: 12V/DC × 2 per column
3. Nominal Capacity: ≥110AH /10HR
4. Discharge Current: ≥110A with 30 minutes (25°C)
5. Starting Current: ≥350A (25°C)
6. Terminal Connection Type: M8 Screw
7. Battery Size: ≤320×170×300 mm
8. Required per column: 2 Batteries